

UC15&M10

Compatible Design

UMTS/HSDPA Module Series

Rev. UC15&M10_Compatible_Design_V1.0

Date: 2013-11-25



Our aim is to provide customers with timely and comprehensive service. For any assistance, please contact our company headquarters:

Quectel Wireless Solutions Co., Ltd.

Office 501, Building 13, No.99, Tianzhou Road, Shanghai, China, 200233

Tel: +86 21 5108 6236

Mail: info@quectel.com

Or our local office, for more information, please visit:

<http://www.quectel.com/support/salesupport.aspx>

For technical support, to report documentation errors, please visit:

<http://www.quectel.com/support/techsupport.aspx>

GENERAL NOTES

QUECTEL OFFERS THIS INFORMATION AS A SERVICE TO ITS CUSTOMERS. THE INFORMATION PROVIDED IS BASED UPON CUSTOMERS' REQUIREMENTS. QUECTEL MAKES EVERY EFFORT TO ENSURE THE QUALITY OF THE INFORMATION IT MAKES AVAILABLE. QUECTEL DOES NOT MAKE ANY WARRANTY AS TO THE INFORMATION CONTAINED HEREIN, AND DOES NOT ACCEPT ANY LIABILITY FOR ANY INJURY, LOSS OR DAMAGE OF ANY KIND INCURRED BY USE OF OR RELIANCE UPON THE INFORMATION. ALL INFORMATION SUPPLIED HEREIN IS SUBJECT TO CHANGE WITHOUT PRIOR NOTICE.

COPYRIGHT

THIS INFORMATION CONTAINED HERE IS PROPRIETARY TECHNICAL INFORMATION OF QUECTEL CO., LTD. TRANSMITTABLE, REPRODUCTION, DISSEMINATION AND EDITING OF THIS DOCUMENT AS WELL AS UTILIZATION OF THIS CONTENTS ARE FORBIDDEN WITHOUT PERMISSION. OFFENDERS WILL BE HELD LIABLE FOR PAYMENT OF DAMAGES. ALL RIGHTS ARE RESERVED IN THE EVENT OF A PATENT GRANT OR REGISTRATION OF A UTILITY MODEL OR DESIGN.

Copyright © Quectel Wireless Solutions Co., Ltd. 2013. All rights reserved.

About the Document

History

Revision	Date	Author	Description
1.0	2013-11-25	Mountain ZHOU	Initial

Contents

About the Document.....	1
Contents	2
Table Index.....	3
Figure Index	4
1 Introduction	5
2 General Descriptions.....	6
2.1. Product Description.....	6
2.2. Pin Assignment	7
3 Pin Description.....	9
3.1. Common Pins.....	9
3.2. Different Functional Pins	11
3.3. Additional pins.....	12
4 Recommended Footprint	13
5 Hardware Reference Design	15
5.1. Power on and off Circuit.....	15
5.2. RESET_N or EMERG_OFF Circuit	15
5.3. Network Status Indication	16
5.4. Operating Status Indication.....	16
5.5. USIM Interface	17
5.6. UART Interface.....	18
5.7. ADC Interface.....	18
5.8. RF Interface	19
5.9. Power Supply	19
6 Appendix A	21

Table Index

TABLE 1: MODULE FREQUENCY BANDS	6
TABLE 2: MODULE GENERAL INFORMATION.....	6
TABLE 3: PARAMETERS	9
TABLE 4: COMMON PINS	9
TABLE 5: DIFFERENT FUNCTIONAL PINS.....	12
TABLE 6: UC15 ADDITIONAL PINS.....	12
TABLE 7: ADC VOLTAGE RANGE.....	18
TABLE 8: RELATED DOCUMENTS.....	21

Quectel
Confidential

Figure Index

FIGURE 1: UC15&M10 PIN ASSIGNMENT	7
FIGURE 2: COMBINED PIN ASSIGNMENT OF UC15&M10	8
FIGURE 3: RECOMMENDED FOOTPRINT (UNIT: MM).....	13
FIGURE 4: RENDERINGS OF INSTALLATION	14
FIGURE 5: POWER ON/OFF THE MODULE USING DRIVING CIRCUIT	15
FIGURE 6: DRIVING CIRCUIT OF RESET_N OR EMERG_OFF	15
FIGURE 7: REFERENCE CIRCUIT OF THE NETLIGHT	16
FIGURE 8: REFERENCE CIRCUIT OF THE STATUS	16
FIGURE 9: REFERENCE DESIGN OF USIM INTERFACE.....	17
FIGURE 10: REFERENCE DESIGN OF UART INTERFACE	18
FIGURE 11: REFERENCE CIRCUIT OF RF INTERFACE	19
FIGURE 12: REFERENCE CIRCUIT OF POWER SUPPLY	20
FIGURE 13: REFERENCE CIRCUIT OF STAR STRUCTURE	20

1 Introduction

UC15 module is compatible with M10 module. This document briefly describes the compatible design of UC15 and M10. UC15 and M10 can be substituted each other in your design and manufacturing.

Quectel
Confidential

2 General Descriptions



2.1. Product Description

The M10 is a Quad-band GSM/GPRS module that works at frequencies of GSM850, EGSM900, DCS1800 and PCS1900. The UC15 is UMTS/HSDPA module includes two series, UC15-A and UC15-E. The following table shows the module frequency bands. UC15 and M10 are designed as compatible products. You can choose the right module for your applications. Under the help of the compatible design guideline, you can migrate your products from M10 2G engine to UC15 3G module smoothly.

Table 1: Module Frequency Bands

Module	Frequency Bands
M10	GSM850/900/1800/1900
UC15-A	GSM850/900/1800/1900, UMTS850/1900
UC15-E	GSM900/1800, UMTS900/2100

Table 2: Module General Information

Module	Appearance	Packaging	Dimensions	Description
UC15		68-pin LCC + 40 other pads	29 x 29 x 2.5mm	UMTS/HSDPA module (UC15-A and UC15-E)
M10		64-pin LCC	29 x 29 x 3.6mm	GSM/GPRS module

2.2. Pin Assignment

The following figure shows the pin assignment of UC15 and M10.




Figure 1: UC15&M10 Pin Assignment

NOTE

The blue pins of UC15 are the additional pins compared with M10.

Figure 2 shows the combination of pin assignment of UC15 and M10.




Figure 2: Combined Pin Assignment of UC15&M10

NOTES

1. The blue pins of UC15 are the additional pins compared with M10.
2. The pin names marked in red in the outside area are M10's.
3. UC15 and M10 are identical in size. The pins of UC15 and M10 are compatible on main functions.

3 Pin Description

This chapter describes the pin definition and assignment of UC15 and M10.

Table 3: Parameters

Symbol	Description
IO	Bidirectional Input / Output
DI	Digital Input
DO	Digital Output
PI	Power Input
PO	Power Output
AI	Analog Input
AO	Analog Output

3.1. Common Pins

The following table shows UC15 and M10's common pins with the same functions.

Table 4: Common Pins

UC15				M10			
Pin NO.	Pin Name	IO	Power Domain	Pin NO.	Pin Name	IO	Power Domain
4	RESERVED	-	-	4	RESERVED	-	-
5	RESERVED	-	-	5	RESERVED	-	-
6	NETLIGHT	DO	2.6V	6	NETLIGHT	DO	2.8V
7	VDD_EXT	PO	2.6V	7	VDD_EXT	PO	2.8V
8	USIM_GND	-	Ground	8	GND	-	Ground

11	USIM_PRESENCE	DI	2.6V	11	SIM_PRESENCE	DI	2.8V
12	USIM_VDD	PO	1.8/3.0V	12	SIM_VDD	PO	1.8/3.0V
13	USIM_DATA	IO	1.8/3.0V	13	SIM_DATA	IO	1.8/3.0V
14	USIM_CLK	DO	1.8/3.0V	14	SIM_CLK	DO	1.8/3.0V
15	USIM_RST	DO	1.8/3.0V	15	SIM_RST	DO	1.8/3.0V
17	RESET_N	DI	1.8V	17	EMERG_OFF	DI	2.8V
18	PWRKEY	DI	1.8V	18	PWRKEY	DI	Pull up to VBAT
19	AGND	-	Ground	19	AGND	-	Ground
20	SPK2P	AO	-	20	SPK2P	AO	-
21	SPK1N	AO	-	21	SPK1N	AO	-
22	SPK1P	AO	-	22	SPK1P	AO	-
23	MIC1P	AI	-	23	MIC1P	AI	-
24	MIC1N	AI	-	24	MIC1N	AI	-
25	MIC2P	AI	-	25	MIC2P	AI	-
26	MIC2N	AI	-	26	MIC2N	AI	-
27	RESERVED			27	RESERVED		
28	RESERVED			28	RESERVED		
29	RESERVED			29	RESERVED		
30	RESERVED			30	RESERVED		
31	RESERVED			31	RESERVED		
32	RESERVED			32	RESERVED		
33	RESERVED			33	RESERVED		
34	RESERVED			34	RESERVED		
35	RESERVED			35	RESERVED		
36	RESERVED	-	-	36	RESERVED	-	-
37	RESERVED			37	RESERVED		

39	RESERVED	-	-	39	RESERVED	-	-
40	ADC1	AI	0~2.1V	40	ADC1	AI	0~2.8V
41	ADC0	AI	0~2.1V	41	ADC0	AI	0~2.8V
42	GND	-	Ground	42	GND	-	Ground
43	RF_ANT	IO	-	43	RF_ANT	IO	-
44	GND	-	Ground	44	GND	-	Ground
45	GND	-	Ground	45	GND	-	Ground
46	GND	-	Ground	46	GND	-	Ground
47	GND	-	Ground	47	GND	-	Ground
48	GND	-	Ground	48	GND	-	Ground
49	GND	-	Ground	49	GND	-	Ground
50	VBAT_RF	PI	3.3~4.3V	50	VBAT	PI	3.3-4.6V
51	VBAT_RF	PI	3.3~4.3V	51	VBAT	PI	3.3-4.6V
52	VBAT_BB	PI	3.3~4.3V	52	VBAT	PI	3.3-4.6V
54	STATUS	DO	2.6V	54	STATUS	DO	2.8V
55	RI	DO	2.6V	55	RI	DO	2.8V
56	DCD	DO	2.6V	56	DCD	DO	2.8V
57	CTS	DO	2.6V	57	CTS	DO	2.8V
58	RTS	DI	2.6V	58	RTS	DI	2.8V
59	DTR	DI	2.6V	59	DTR	DI	2.8V
60	TXD	DO	2.6V	60	TXD	DO	2.8V
61	RXD	DI	2.6V	61	RXD	DI	2.8V

3.2. Different Functional Pins

The following table shows the different functional pins of UC15 compared with M10 at the same pin location.

Table 5: Different Functional Pins

UC15				M10			
Pin NO.	Pin Name	IO	Power Domain	Pin NO.	Pin Name	IO	Power Domain
1	RESERVED	-	-	1	SD_DATA	IO	2.8V
2	AP_READY	DO	2.6V	2	SD_CLK	DO	2.8V
3	RESERVED	-	-	3	SD_CMD	DO	2.8V
9	RESERVED	-	-	9	DBG_RXD	DI	2.8V
10	RESERVED	-	-	10	DBG_TXD	DO	2.8V
16	RESERVED	-	-	16	VRTC	IO	1.5~3.3V
38	RESERVED	-	-	38	GPIO1	IO	2.8V
53	VBAT_BB	PI	3.3~4.3V	53	RESERVED		
62	USB_DP	IO	-	62	TXD3	DO	2.8V
63	USB_DM	IO	-	63	RXD3	DI	2.8V
64	USB_VBUS	PI	Typ.5V	64	GPIO0	IO	2.8V

NOTE

For different functional pins, if necessary, reserve 0 ohm resistors.

3.3. Additional pins

Table 6: UC15 Additional pins

PIN NO.	Pin Name	IO	Pin Description
65,67~68, 81~108	GND	-	Ground
66,69~80	RESERVED	-	-

NOTES

1. All of GND pins should be connected to ground.
2. Keep all RESERVED and unused pins unconnected except pin 53 on M10.

4 Recommended Footprint

The following figure shows the recommended compatible footprint of UC15 and M10.




Figure 3: Recommended Footprint (Unit: mm)

The following figure shows the sketch map of installation between UC15 and M10.




Figure 4: Renderings of Installation

5 Hardware Reference Design

The following chapters describe compatible design of UC15 and M10 on main functionalities.

5.1. Power on and off Circuit




Figure 5: Power on/off the Module Using Driving Circuit

5.2. RESET_N or EMERG_OFF Circuit




Figure 6: Driving Circuit of RESET_N or EMERG_OFF

NOTE

As to UC15, the pulse time of reset must be between 50ms and 200ms.

5.3. Network Status Indication

The NETLIGHT signal can be used to drive a network status indicator LED. The following circuit is the reference design of NETLIGHT.




Figure 7: Reference Circuit of the NETLIGHT

5.4. Operating Status Indication

The STATUS pin is set as the module status indicator and can be used to judge whether module is power-on or not. It will output high level when module works normally. The following figure shows the reference circuit of driving LED for module.




Figure 8: Reference Circuit of the STATUS

5.5. USIM Interface

USIM interface of UC15 and M10 supports 1.8V or 3.0V USIM/SIM cards automatically. The following figure shows the USIM reference design with USIM card detection function.




Figure 9: Reference Design of USIM Interface

5.6. UART Interface

The following circuit shows reference design of UART interface level match between UC15 and 3.3V system. When M10 is applied, these 3.6K resistors should be changed to 5.6K.




Figure 10: Reference Design of UART Interface

NOTES

1. UC15's UART pins belong to 2.6V power domain.
2. M10's UART pins belong to 2.8V power domain.

5.7. ADC Interface

Both UC15 and M10 have two ADC pins for general purpose analog-to-digital converter. But there are some differences in voltage range. The following table shows the differences between UC15 and M10.

Table 7: ADC Voltage Range

Channel	UC15	M10
ADC0	0~2.1V	0~2.8V
ADC1	0~2.1V	0~2.8V

5.8. RF Interface

Pin 43 is the RF antenna pad. The RF interface has an impedance of 50Ω . A reference circuit is shown in the following figure. In order to adjust RF performance, it should reserve a π -type matching circuit. By default, the resistance of R1 is 0Ω and capacitors C1 and C2 are not installed.




Figure 11: Reference Circuit of RF Interface

5.9. Power Supply

The power supply range of the M10 module is 3.3V to 4.6V and the power supply range of the UC15 is 3.3V to 4.3V. Attention should be paid in the range of the power source to make sure that the input voltage will never drop below 3.3V and never exceed 4.3V, and the typical power supply of UC15 is 3.8V. The following figure shows a reference design for +5V input power source. The designed output for the power supply is 3.88V and the maximum load current is 3A. The VBAT to UC15 VBAT_BB and VBAT_RF pins should be divided into two separated paths in star structure. It is also applicable to M10. In addition, in order to get a stable output voltage, it is suggested to use a zener diode whose reverse zener voltage is 5.1V and dissipation power is more than 0.5 watt.




Figure 12: Reference Circuit of Power Supply




Figure 13: Reference Circuit of Star Structure

NOTE

When M10 is applied, pin 53 of M10 can be connected to VBAT_BB here.

6 Appendix A

Table 8: Related Documents

SN	Document name	Remark
[1]	UC15_Hardware_Design	UC15 Hardware Design
[2]	M10_Hardware_Design	M10 Hardware Design
[3]	UC15&M10_Reference_Design	UC15 and M10 Compatible Reference Design